

FOR ALL HEAVY DUTY GAS OR DIESEL ENGINES UP TO 960 CU IN:

\$49.95

Since 1975, this unique proven formula has been providing full-time protection and improved performance. Lubrilon's proprietary formulation chemically bonds a micro-thin Permafused™ Lubricant film to all metal surfaces inside an engine. Lubrilon reacts only with Pfl™ activated metal, leaving no build up that could change tolerances or alter oil flow. It is unequaled by modern day motor oils, synthetic lubricants, oil additives, moly or PTFE type engine treatments. The use of Lubrilon's Permanent Engine Protection will not void manufacturer's engine warranty. This one-time use product protects and extends the life of your engine. [32oz bottle](#)

**Overall Performance Benefits:**

- Protects** from Oil Shear, Oil Loss, Additive Breakdown, Acids, Dry Starts
- Improves** Compression, Horsepower, Fuel Mileage, Engine Life, Cold Weather Starts
- Reduces** Noise, Wear, Friction, Oil Consumption, Amp Draw, Idle Over heating, Corrosion

FOLLOW THESE DIRECTIONS EXACTLY TO ENSURE THE BEST PERFORMANCE IMPROVEMENT



**A few things to know before you get started:**

Lubrilon's permanent engine protection is compatible with all crude based and synthetic based engine oils of all viscosities. .

For new and rebuilt engines: Do not use our Lubrilon's Permanent Engine Protection until you have reached at least 5,000 miles and the rings have seated (had a chance to form to the cylinder walls). This does not apply to diesel engines up to 960 cu in or 14.6 liters

For optimum performance and protection we recommend that you retreat every 100,000 miles. Do not mix our product with another. If your transmission has some other kind of treatment in it we recommend that you first change the fluids and then add our products.

We strongly recommend that you keep up your manufacturers' maintenance program. Changing fluids regularly is the key to successful car maintenance.

**Directions for Permanent Engine Protection:**

- 32 oz will treat a gas or diesel engine that takes up to 12 quarts of oil:
- For engines that use more than 12 quarts add at about a 10% ratio. (see chart below)
- Drain oil and change filter.
- Add 10 quarts of quality petroleum or synthetic motor oil.
- Add 32 oz of Lubrilon's permanent engine protection.
- Top oil off to manufacturer's recommended capacity.
- Start and run engine for 10 minutes to blend.
- Drive normally and maintain proper oil level.

**CAUTION: KEEP OUT OF REACH OF CHILDREN**

Harmful if swallowed. Do not induce vomiting. Seek medical attention. Wash hands thoroughly with soap and water after use.